

N 50, WARMING DRAWER, 60 X 14 CM, GRAPHITE-GREY N1AHA01G0B



- $\sqrt{}$ Stepless temperature control The warming drawer makes choosing easy with our stepless temperature control from $40^{\circ}\text{-}80^{\circ}\text{C}.$
- $\sqrt{}$ Installation with compact appliance combine your drawer with any 45 cm appliance

Features Technical Data

Built-in / Free-standing: Built-in Maximum number of espresso cups: 64
Dimensions: 140x594x540 mm
Dimensions of the packed product (HxWxD): 210x660x660 mm
Required niche size for installation (HxWxD): 140 x 560 x 550 mm
EAN code: 4242004262688
Fuse protection: 6 A
Voltage: 220-240 V





N 50, WARMING DRAWER, 60 X 14 CM, GRAPHITE-GREY N1AHA01G0B

Features

Design

- Bevelled oval controls With Steel Trim
- User-friendly electronics: extremely
- easy and comfortable operation
- Cavity inner surface: stainless steel
- Push-Pull opening mechanism

Programmes/functions

- 4 Functions: keeping drinks and food warm, pre-warming of tableware, yeast dough proving, thawing of delicate foods
- Loading up to 15 kg
- Can accommodate up to:
- -14plates
- -64 espresso cups

Accessories

• 1 x anti-slip mat


Performance/technical information

- Cavity volume: 23 I
- 150 cm Cable Cable length
- Total connected load electric: 0.4 KW
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 140 mm x 594 mm x 540 mm
- \bullet Niche dimension (hxwxd): 140 mm x 560 mm 568 mm x 550 mm
- Ventilation requirements please refer to the installation manual prior to fitting



N 50, WARMING DRAWER, 60 X 14 CM, GRAPHITE-GREY N1AHA01G0B

Dimensioned drawings



Compact ovens with an appliance height of 455 mm can be installed above a warming drawer.
An intermediate floor is not required.

measurements in mm

