

N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27CS59S0





Optional accessories

Z2402X0 Small pot supportZ2471X0 Wok ringZ2480X0 Simmer plate

The gas hob with a tempered glass surface and adjustable FlameSelect.

- $\sqrt{}$ Tempered Glass Surface extremely easy-to-clean surface.
- $\sqrt{\text{FlameSelect}^{\otimes}}$ Gain ultimate control of your flame.
- $\sqrt{\mbox{ Pan Supports}}$ continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{\text{Wok Burner powerful cooking at up to 4 kW}}$.
- $\sqrt{\,}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.

Features

Technical Data	
Product name/family:	gas hob w
integrated controls	
Built-in / Free-standing:	Built-in
Energy input:	Gas
Number of cooking zones:	5
Type of control setting devices:	
Required niche size for installation (HxWxD): . 480-492 mm	45 x 560-562 x
100 132 111111	752
Width of the appliance:	
Dimensions:	
Dimensions of the packed product (HxWxD): .	
Net weight:	
Gross weight:	
Residual heat indicator:	without
Location of control panel:	Front
Basic surface material:	Tempered glass
Color of surface:	Black
Color of frame:	Black
Length electrical supply cord:	100 cm
EAN code:	4242004203476
Gas connection rating:	11500 W
Fuse protection:	3 A
Voltage:	220-240 V
Frequency:	





N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27CS59S0

Features

Design

- tempered glass surface, black
- Two built-in options:
- - Flush installation
- - Surface mounted installation: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports with rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 58 x 752 x 520
- • Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 - 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 11.5 KW



N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27CS59S0

