

N 90, GAS HOB, 90 CM, CERAMIC, BLACK T29TS79N0





Optional accessories

Z2402X0 Small pot support Z2480X0 Simmer plate

The gas hob with heat-resistant ceramic glass surface and adjustable FlameSelect control.

- $\sqrt{\mbox{ Ceramic Glass Surface}}$ extremely easy-to-clean surface.
- √ FlameSelect® Gain ultimate control of your flame.
- $\sqrt{\mbox{ Pan Supports}}$ continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{\,}$ Dual Wok Burner 6.0 kW Use one gas flame for simmering, two for sizzling stir-fries.
- $\sqrt{\,}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.

Features

Technical Data Product name/family:gas hob w integrated controls Built-in / Free-standing: Built-in Energy input: Gas Type of control setting devices:sword knobs Required niche size for installation (HxWxD):45 x 850-852 x 490-502 mm Dimensions of the packed product (HxWxD): ...165x1116x659 mm Residual heat indicator:without Location of control panel:Front Basic surface material: Ceramic Color of surface:Black, Stainless steel Color of frame:Black, Stainless steel Voltage:220-240 V Frequency:50; 60 Hz





N 90, GAS HOB, 90 CM, CERAMIC, BLACK T29TS79N0

Features

Desian

- ceramic glass surface, black
- Bevelled design, stainless steel
- black cast iron pan supports with protective rubber feet
- Low profile burner: elegant burner design

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Pan supports dishwasher safe: clean without effort in the dishwasher.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left: Wok burner up to 6.1 KW (depending on gas type)
- Center front: Standard burner up to 1.9 KW (depending on gas type)
- Center rear: Economy burner up to 1.1 KW (depending on gas type)
- Right rear: High speed burner up to 2.8 KW (depending on gas type)
- Right front: Standard burner up to 1.9 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 59 x 918 x 546
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 502)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 13.8 KW

Accessories

ullet 1 x WOK attachment ring included



N 90, GAS HOB, 90 CM, CERAMIC, BLACK T29TS79N0

