
N 70, induction hob, 80 cm, T48FD23X0





Induction	Width (cm)	Combi Induction
	■ 80	

Optional accessories

Z943SE0 Set of 2 pots and 1 pan

Standalone induction cooktop with TouchControl.

- $\checkmark\,$ Touch Control a convenient way to control hobs with just one touch.
- $\sqrt{}\,$ Power Move the combi zone offers two heating zones: boiling in front and warming in the rear.
- $\checkmark\,$ Power Boost optimized power level function for more flexible and even faster heating.
- √ Induction the heat is generated directly in the cookware for precise cooking that stops when power is off.

Features

Technical Data Product name/family : Cooking zone ceramic Construction type : Built-in Energy input : Electric Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : $51 \times 750-750 \times$ 490-500 Appliance Width (mm): 802 Dimensions of the product (mm) : 51 x 802 x 522 Dimensions of the packed product (HxWxD) (mm) : 126 × 953 × 603 Net weight (kg) : 15.303 Gross weight (kg) : 16.8 Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black Approval certificates : AENOR, CE Length electrical supply cord (cm) : 110 EAN code : 4242004195597 Electrical connection rating (W): 7400 Voltage (V) : 220-240 Frequency (Hz) : 50; 60



N 70, induction hob, 80 cm, T48FD23X0

Features

Control

• Touch control

Flexibility

- Combi zone
- 5 zone induction hob

Special features

- Boost setting for all zones
- Variable 17-stage power settings for each zone
- Digital display of cooking levels
- 2 stage residual heat indicators
- Timer with automatic shut off for all zones LED timer for each zone with switch off function and acoustic signal
- ReStart function
- Automatic pan recognition Safety cut out facility Control panel lock Control panel suspension
- Keep warm function
- Energy consumption display

Technical information

- Cooking zones: 1 x Ø 180 mm, 1.8 KW (max. Power levels 3.1 KW) Induction; 1 x Ø 145 mm, 1.4 KW (max. Power levels 2.2 KW) Induction; 1 x Ø 240 mm, 2.2 KW (max. Power levels 3.7 KW) Induction; 1 x Ø 210 mm, 2.2 KW (max. Power levels 3.7 KW) Induction; 1 x Ø 210 mm, 2.2 KW (max. Power levels 3.7 KW) Induction
- Measurement: (H/W/D) 51 x 802 x 522 mm
- Installation dimensions: (ID/W/D) 51 mm x 750 mm x 490 mm
- 80 cm width
- Length wire connection: 110 cm
- Main switch
- Min. worktop thickness: 16 mm
- Output 7400 W
- Cable included in packaging