


# N 70, INDUCTION HOB, 60 CM, BLACK, T56FD50X0







#### Optional accessories Z9404SE0 4 pieces Set Z9406SE0 6 pieces Set Z9410ES0 Espresso maker 4 cups Z9410X1 Stainless Steel roaster with glas lid Steaming Rack for Stainless Steel roaste Z9415X1 Z9416X2 Griddle Plate Z9417X2 Teppan Yaki (large) Z9428FE0 Iron pan Ø 18 / 28 cm Z943SE0 Set of 2 pots and 1 pan

# FlexInduction hob with TouchControl.

- $\sqrt{\phantom{a}}$  Touch Control Control your hob with a simple touch.
- $\sqrt{\mbox{Flex Induction}}$  Your hob detects and heats your individual cookware.
- $\sqrt{\mbox{ Power Boost}}$  An extra surge of heat when you need fast results.
- $\sqrt{}$  Induction the heat is generated directly in the cookware for precise cooking that stops when power is off.

#### Features

# **Technical Data**

Product name/family:	Cooking zone ceramic
Built-in / Free-standing:	
Energy input:	Electric
Number of cooking zones:	
Min. required niche size for installati	on (HxWxD): 51 x 560-560 x
490-500 mm	
Width of the appliance:	592 mm
Dimensions:	51 x 592 x 522 mm
Dimensions of the packed product (	HxWxD): . 126 x 753 x 603 mm
Net weight:	11.9 kg
Gross weight:	14.2 kg
Residual heat indicator:	Separate
Location of control panel:	Front
Basic surface material:	Ceramic
Color of surface:	Black
Length electrical supply cord:	110.0 cm
EAN code:	4242004195689
Voltage:	220-240 V
Frequency:	50; 60 Hz





# N 70, INDUCTION HOB, 60 CM, BLACK, T56FD50X0

# Features

#### Design

- · Bevelled front edge
- 60 cm: space for 4 pots or pans.

#### Flexibility of cooking zones

- Flex Induction: use cookware of any shape or size anywhere within the 40cm long zone.
- Cooking zone front left: 240 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 240 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 145 mm , 1.4 KW (max power 2.2 KW)
- Cooking zone front right: 210 mm, 2.2 KW (max. power 3.7 KW)

#### Usage convenience

- Touch control: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones
- : switches off the cooking zone at the end of the time set (e.g. for boiled eqqs).
- LED timer for each zone with switch off function and acoustic signal
- : an alarm sounds at the end of the time set (e.g. for pasta).

# Time saving & efficiency

- Power Boost function for all zones
- : boil water faster thanks to 50% more energy than at the highest standard level.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds

# Safety

- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

# Installation

- Dimensions of the product (HxWxD mm): 51 x 592 x 522
- Required niche size for installation (HxWxD mm) : 51 x 560 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- 4.6kW power output (20A); current management options for 16A, 13A or 10A connection: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, Cable included in packaging



# N 70, INDUCTION HOB, 60 CM, BLACK, T56FD50X0

