N 70, Built-in oven, Stainless steel B27CR22N1B





Shift Control
Heating Methods
Efficient
Easy Clean

Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control

Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control

Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control

Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control

Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control

Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control
Image: Shift Control

Optional accessories

711CR10X0	Baking and roasting grid (standard)
	5 55 ,
ZTISZOUXO	SeamlessCombination mounting kit
Z11TC10X0	ComfortFlex Rail (1 level)
Z11TC16X0	ComfortFlex Rail (1 level)
Z12CB10A0	Baking tray, anthracite enamelled
Z12CM10A0	Moussaka pan, anthracite enamelled
719DD10X0	Steam set for ovens

Built-in oven with CircoTherm - NEFF's award-winning hot air system.

- $\checkmark\,$ CircoTherm NEFF's outstanding hot-air system for simultaneous baking and roasting on up to 3 levels.
- $\checkmark\,$ The perfect duo for cleaning: Pyrolysis after heavy use and EasyClean the environment-saving option for fast oven cleaning.
- $\sqrt{}$ ShiftControl fast navigation through menus and simple operation with the TFT display.
- √ Hinged door

Features

Technical Data Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Integrated Cleaning system : Hydrolytic, Pyrolytic Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550 Dimensions of the product (mm) : 595 x 596 x 548 Dimensions of the packed product (HxWxD) (mm) : 670 x 680 x 670 Control Panel Material : Stainless steel Door Material : Glass Net weight (kg) : 37.772 Usable volume of cavity (I) : 71 Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Dough proving setting, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting Oven control : electronic Number of interior lights : 1 Approval certificates : CE, VDE Length electrical supply cord (cm) : 120 EAN code : 4242004197287 Number of cavities (2010/30/EC) : 1 Energy efficiency class (2010/30/EC) : A+ Energy consumption per cycle conventional (2010/30/EC) : 0.87 Energy consumption per cycle forced air convection (2010/30/EC) : 0.69 Energy efficiency index (2010/30/EC) : 81.2 Connection Rating (W): 2990 Current (A) : 13 Voltage (V) : 220-240 Frequency (Hz) : 50; 60 Plug type : no plug



N 70, Built-in oven, Stainless steel B27CR22N1B

Features

Heating Functions

- Oven with 12 heating methods:
- 4D hot air CircoTherm Eco Top/Bottom heating
- Top/bottom heating Eco
- Hot-air grilling
- Full surface grill
- Small area grill Pizza setting
- Bread Baking
- Bottom heating
- Slow cooking
- Dough proving
- Temperature range 40 °C 275 °C
- Cavity volume: 71 litres

Design

- lilluminated ShiftControl
- Anthracite enamel cavity with 4 shelf positions

Cleaning

- Pyrolytic self cleaning
- EasyClean Cleaning program

•

Convenience

- Temperature proposal Actual temperature display Optical temperature control Sabbath setting
- Additional functions: Steam cooking function (system steamer accessory required)
- Electronic clock
- Rapid heating-up
- LED lighting
- Cooling fan
- Stainless-steel fan
- Info button
- Bar handle
- Cavity with shelf support rails, Telescopic slide-out Accessory

Accessories

• 2 x combination grid, 1 x universal pan

Cleaning

• Individual adjustable child lock Residual heat indicator Safety switch off

Technical Information

- Length of mains cable: 120 cm
- Total connected load electric: 2.99 KW
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing